

WAND - Installation Guide

The **WAND** Module allows your X2 Controller to connect to the internet via a Wi-Fi router. Once

connected, you can access and manage the controller with your smartphone, tablet, or computer. To connect the X2 controller to the Hydrawise app using the WAND device, you can follow the in-app step instructions. Review the chart below to verify compatibility between the WAND device and the X2 Controller.

Model	Controller Date Code	Wand Date Code
X2 Controller	June 2022 Older	Compatible with all WANDs
	July 2022 Newer	DEC 2022 or newer Only WANDs





X2[™] Controllers

Date code is located under the wiring terminal strip.


WAND Wi-Fi Modules

Date code is located on the back side of the module. **(mo/yr)**

Step 1: WiFi Signal - A medium to high signal strength is preferred to maintain a stable connection between the controller and the router. In some cases, a Wi-Fi extender should be installed to increase the signal. <u>Learn</u> More



Step 2: Installing the WAND Module - Remove the cartridge cover on the X2 Controller. Insert the WAND device. All programming is now managed via cloud-based Hydrawise Software from a smartphone, tablet, or desktop browser.




Step 3: Navigating the WAND Module with the X2 Controller- Make a note of the serial number on the WAND device.

Locate the following:

A. Wi-Fi status LED

B. Wi-Fi setup button

C. WAND serial number





Step 5: Adding your controller -

- 1. After registering, click the "Let's Get Started" button in the message sent to your email account.
- 2. Click the "Let's Get Started" button again on your Hydrawise App or website screen.
- 3. Continue following all in-app steps to add your X2 Controller to Hydrawise.

