



WAND - Installation Guide

The **WAND** Module allows your X2 Controller to connect to the internet via a Wi-Fi router. Once connected, you can access and manage the controller with your smartphone, tablet, or computer. To connect the X2 controller to the Hydrowise app using the WAND device, you can follow the in-app step instructions. Review the chart below to verify compatibility between the WAND device and the X2 Controller.

Model	Controller Date Code	Wand Date Code
X2 Controller	June 2022 Older	Compatible with all WANDs
	July 2022 Newer	DEC 2022 or newer Only WANDs

□ **Step 1: WiFi Signal** - A medium to high signal strength is preferred to maintain a stable connection between the controller and the router. In some cases, a Wi-Fi extender should be installed to increase the signal. [Learn More](#) [1]

□ **Step 2: Installing the WAND Module** - Remove the cartridge cover on the X2 Controller. Insert the WAND device. All programming is now managed via cloud-based Hydrowise Software from a smartphone, tablet, or desktop browser.

□ **Step 3: Navigating the WAND Module with the X2 Controller** - Make a note of the serial number on the WAND device. Locate the following:
A. Wi-Fi status LED
B. Wi-Fi setup button
C. WAND serial number

□ **Step 4: Access Hydrowise Software** - Download the Hydrowise app from the Apple® App Store or Google Play™ Store, or log on to hydrowise.com. [2] Log into your account. If this is the first time you have logged in, you will be guided through a setup wizard to help you with an initial configuration of your controller.

□ **Step 5: Adding your controller -**
1. After registering, click the “Let's Get Started” button in the message sent to your email account.
2. Click the “Let's Get Started” button again on your Hydrowise App or website screen.
3. Continue following all in-app steps to add your X2 Controller to Hydrowise.

□